## Kitsune General Specification Sheet



## Bluetooth

Bluetooth 4.2, Class 2

Dual Mode: Bluetooth and Bluetooth Low Energy Frequency Bands: 2,402 MHz to 2480 MHz Operating Range: Maximum 20m to 30m

Output Power: Class 2 (BER/EDR) up to +4 dBm,

BLE up to +10 dBm

Bluetooth Profiles Supported: A2DP, AVRCP



13.56 MHz RFID Reader/Writer Compliant with ISO/IEC 14443 A And B NFC Forum Device Types 1-4 Output Power +20 dBm (100mW) at 10cm Functionality Pending Development



Loudspeaker Mode: 8hrs Headset Mode: 18hrs

Idle: 24hrs





## **Audio**

Group Mode: Mono, Output Power up to 1W

Headset Mode: Stereo,

Output Power: Up to 125mW

Environmental Hearing Mode: Stereo Speaker Output Range: 400 Hz to 9000 Hz Speaker Sensitivity: 90 dBA SPL at 10cm

## **Certifications**

Bluetooth: 4.2 Audio Module Bluetooth: SIG Certified

Modular approval: FCC and IC (Canada) - BT

Compliant: Part 15 of the FCC Rules

FCC ID: SSS-BC11X

Compliant: Industry Canada license-exempt RSS

standard(s): IC ID: 11012A-BC11X

NFC Functionality Pending FCC and IC approval